

# [ SEQ CHAPTER \H \R 1]FEDERAL OPERATING PERMIT

A FEDERAL OPERATING PERMIT IS HEREBY ISSUED TO  
Huntsman Petrochemical LLC

AUTHORIZING THE OPERATION OF  
Huntsman Port Neches  
E3/E6 Units  
Petrochemical Manufacturing

LOCATED AT  
Jefferson County, Texas  
Latitude 29° 58' 5" Longitude 93° 55' 35"  
Regulated Entity Number: RN100219252

This permit is issued in accordance with and subject to the Texas Clean Air Act (TCAA), Chapter 382 of the Texas Health and Safety Code and Title 30 Texas Administrative Code Chapter 122 (30 TAC Chapter 122), Federal Operating Permits. Under 30 TAC Chapter 122, this permit constitutes the permit holder's authority to operate the site and emission units listed in this permit. Operations of the site and emission units listed in this permit are subject to all additional rules or amended rules and orders of the Commission pursuant to the TCAA.

This permit does not relieve the permit holder from the responsibility of obtaining New Source Review authorization for new, modified, or existing facilities in accordance with 30 TAC Chapter 116, Control of Air Pollution by Permits for New Construction or Modification.

The site and emission units authorized by this permit shall be operated in accordance with 30 TAC Chapter 122, the general terms and conditions, special terms and conditions, and attachments contained herein.

This permit shall expire five years from the date of issuance. The renewal requirements specified in 30 TAC § 122.241 must be satisfied in order to renew the authorization to operate the site and emission units.

Permit No: 02286 Issuance Date: \_\_\_\_\_

\_\_\_\_\_  
For the Commission

## Table of Contents

Section	Page
[ TOC \o "1-3" \h \z \t "SOP_Heading1,1,SOP_Heading2,2,SOP_Heading2 + Centered,2,SOP_Heading1 + Centered,1" ]	

## **General Terms and Conditions**

The permit holder shall comply with all terms and conditions contained in 30 TAC § 122.143 (General Terms and Conditions), 30 TAC § 122.144 (Recordkeeping Terms and Conditions), 30 TAC § 122.145 (Reporting Terms and Conditions), and 30 TAC § 122.146 (Compliance Certification Terms and Conditions).

In accordance with 30 TAC § 122.144(1), records of required monitoring data and support information required by this permit, or any applicable requirement codified in this permit, are required to be maintained for a period of five years from the date of the monitoring report, sample, or application unless a longer data retention period is specified in an applicable requirement. The five year record retention period supersedes any less stringent retention requirement that may be specified in a condition of a permit identified in the New Source Review Authorization attachment.

If the permit holder chooses to demonstrate that this permit is no longer required, a written request to void this permit shall be submitted to the Texas Commission on Environmental Quality (TCEQ) by the Responsible Official in accordance with 30 TAC § 122.161(e). The permit holder shall comply with the permit's requirements, including compliance certification and deviation reporting, until notified by the TCEQ that this permit is voided.

The permit holder shall comply with 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit.

All reports required by this permit must include in the submittal a cover letter which identifies the following information: company name, TCEQ regulated entity number, air account number (if assigned), site name, area name (if applicable), and Air Permits Division permit number(s).

## **[ SEQ CHAPTER \h \r 1]Special Terms and Conditions:**

### **Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting**

1. Permit holder shall comply with the following requirements:
  - A. Emission units (including groups and processes) in the Applicable Requirements Summary attachment shall meet the limitations, standards, equipment specifications, monitoring, recordkeeping, reporting, testing, and other requirements listed in the Applicable Requirements Summary attachment to assure compliance with the permit.
  - B. The textual description in the column titled "Textual Description" in the Applicable Requirements Summary attachment is not enforceable and is not deemed as a substitute for the actual regulatory language. The Textual Description is provided for information purposes only.
  - C. A citation listed on the Applicable Requirements Summary attachment, which has a notation [G] listed before it, shall include the referenced section and subsection for all commission rules, or paragraphs for all federal and state regulations and all subordinate paragraphs, subparagraphs and clauses, subclauses, and items contained within the referenced citation as applicable requirements.
  - D. When a grouped citation, notated with a [G] in the Applicable Requirements Summary, contains multiple compliance options, the permit holder must keep records of when each compliance option was used.

- E. Emission units subject to 40 CFR Part 63, Subpart PPP as identified in the attached Applicable Requirements Summary table are subject to 30 TAC Chapter 113, Subchapter C, § 113.730 which incorporates the 40 CFR Part 63 Subpart by reference.
2. The permit holder shall comply with the following sections of 30 TAC Chapter 101 (General Air Quality Rules):
- A. Title 30 TAC § 101.1 (relating to Definitions), insofar as the terms defined in this section are used to define the terms used in other applicable requirements
  - B. Title 30 TAC § 101.3 (relating to Circumvention)
  - C. Title 30 TAC § 101.8 (relating to Sampling), if such action has been requested by the TCEQ
  - D. Title 30 TAC § 101.9 (relating to Sampling Ports), if such action has been requested by the TCEQ
  - E. Title 30 TAC § 101.10 (relating to Emissions Inventory Requirements)
  - F. Title 30 TAC § 101.201 (relating to Emission Event Reporting and Recordkeeping Requirements)
  - G. Title 30 TAC § 101.211 (relating to Scheduled Maintenance, Start-up, and Shutdown Reporting and Recordkeeping Requirements)
  - H. Title 30 TAC § 101.221 (relating to Operational Requirements)
  - I. Title 30 TAC § 101.222 (relating to Demonstrations)
  - J. Title 30 TAC § 101.223 (relating to Actions to Reduce Excessive Emissions)
3. Permit holder shall comply with the following requirements of 30 TAC Chapter 111:
- A. Visible emissions from stationary vents with a flow rate of less than 100,000 actual cubic feet per minute that are not listed in the Applicable Requirements Summary attachment for 30 TAC Chapter 111, Subchapter A, Division 1, shall not exceed 20% opacity averaged over a six minute period. The permit holder shall comply with the following requirements for stationary vents at the site subject to this standard:
    - (i) Title 30 TAC § 111.111(a)(1)(B) (relating to Requirements for Specified Sources)
    - (ii) Title 30 TAC § 111.111(a)(1)(E)
    - (iii) Title 30 TAC § 111.111(a)(1)(F)(i), (ii), (iii), or (iv)
    - (iv) For emission units with vent emissions subject to 30 TAC § 111.111(a)(1)(B), complying with 30 TAC § 111.111(a)(1)(F)(ii), (iii), or (iv), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO<sub>x</sub>, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146. These periodic monitoring requirements do not apply to vents that are not capable of producing visible emissions such as vents that emit only colorless VOCs; vents from non-fuming liquids; vents that provide passive ventilation, such as plumbing vents; or vent emissions from any other source that



does not obstruct the transmission of light. Vents, as specified in the "Applicable Requirements Summary" attachment, that are subject to the emission limitation of 30 TAC § 111.111(a)(1)(B) are not subject to the following periodic monitoring requirements:

- (1) An observation of stationary vents from emission units in operation shall be conducted at least once during each calendar quarter unless the emission unit is not operating for the entire quarter.
- (2) For stationary vents from a combustion source, if an alternative to the normally fired fuel is fired for a period greater than or equal to 24 consecutive hours, the permit holder shall conduct an observation of the stationary vent for each such period to determine if visible emissions are present. If such period is greater than 3 months, observations shall be conducted once during each quarter. Supplementing the normally fired fuel with natural gas or fuel gas to increase the net heating value to the minimum required value does not constitute creation of an alternative fuel.
- (3) Records of all observations shall be maintained.
- (4) Visible emissions observations of emission units operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of emission units operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions observations shall be made during times when the activities described in 30 TAC § 111.111(a)(1)(E) are not taking place. Visible emissions shall be determined with each stationary vent in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each stationary vent during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.
- (5) Compliance Certification:
  - (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(1) and (a)(1)(B).
  - (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is

determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

- (c) Some vents may be subject to multiple visible emission or monitoring requirements. All credible data must be considered when certifying compliance with this requirement even if the observation or monitoring was performed to demonstrate compliance with a different requirement.

B. For visible emissions from a building, enclosed facility, or other structure; the permit holder shall comply with the following requirements:

- (i) Title 30 TAC § 111.111(a)(7)(A) (relating to Requirements for Specified Sources)
- (ii) Title 30 TAC § 111.111(a)(7)(B)(i) or (ii)
- (iii) For a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source subject to 30 TAC § 111.111(a)(7)(A), complying with 30 TAC § 111.111(a)(7)(B)(i) or (ii), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO<sub>x</sub>, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146:
  - (1) An observation of visible emissions from a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source which is required to comply with 30 TAC § 111.111(a)(7)(A) shall be conducted at least once during each calendar quarter unless the air emission source or enclosed facility is not operating for the entire quarter.
  - (2) Records of all observations shall be maintained.
  - (3) Visible emissions observations of air emission sources or enclosed facilities operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of air emission sources or enclosed facilities operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions shall be determined with each emissions outlet in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each emissions outlet during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.

(4) Compliance Certification:

- (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(7) and (a)(7)(A)
- (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(7)(B) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

C. For visible emissions from all other sources not specified in 30 TAC § 111.111(a)(1), (4), or (7); the permit holder shall comply with the following requirements:

- (i) Title 30 TAC § 111.111(a)(8)(A) (relating to Requirements for Specified Sources)
- (ii) Title 30 TAC § 111.111(a)(8)(B)(i) or (ii)
- (iii) For a source subject to 30 TAC § 111.111(a)(8)(A), complying with 30 TAC § 111.111(a)(8)(B)(i) or (ii), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO<sub>x</sub>, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146:
  - (1) An observation of visible emissions from a source which is required to comply with 30 TAC § 111.111(a)(8)(A) shall be conducted at least once during each calendar quarter unless the source is not operating for the entire quarter.
  - (2) Records of all observations shall be maintained.
  - (3) Visible emissions observations of sources operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of sources operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions shall be determined with each source in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each source during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer

visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.

(4) Compliance Certification:

- (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(8) and (a)(8)(A)
- (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(8)(B) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

- D. Certification of opacity readers determining opacities under Method 9 (as outlined in 40 CFR Part 60, Appendix A) to comply with opacity monitoring requirements shall be accomplished by completing the Visible Emissions Evaluators Course, or approved agency equivalent, no more than 180 days before the opacity reading.
- E. For emission units with contributions from uncombined water, the permit holder shall comply with the requirements of 30 TAC § 111.111(b).
- F. Emission limits on nonagricultural processes, except for the steam generators specified in 30 TAC § 111.153, shall comply with the following requirements:
  - (i) Emissions of PM from any source may not exceed the allowable rates as required in 30 TAC § 111.151(a) (relating to Allowable Emissions Limits)
  - (ii) Sources with an effective stack height ( $h_e$ ) less than the standard effective stack height ( $H_e$ ), must reduce the allowable emission level by multiplying it by  $[h_e/H_e]^2$  as required in 30 TAC § 111.151(b)
  - (iii) Effective stack height shall be calculated by the equation specified in 30 TAC § 111.151(c)
- 4. For storage vessels maintaining working pressure as specified in 30 TAC Chapter 115, Subchapter B, Division 1: "Storage of Volatile Organic Compounds," the permit holder shall comply with the requirements of 30 TAC § 115.112(a)(1).
- 5. The permit holder shall comply with the following requirements of 30 TAC Chapter 115, Subchapter F, Division 3, Degassing of Storage Tanks, Transport Vessels and Marine Vessels:

- A. For degassing of stationary VOC storage tanks, the permit holder shall comply with the following requirements:
- (i) Title 30 TAC § 115.541(a) - (c) (relating to Emission Specifications)
  - (ii) Title 30 TAC § 115.541(f) (relating to Emission Specifications), for floating roof storage tanks
  - (iii) Title 30 TAC § 115.542(a) and (a)(1), (a)(2), (a)(3) or (a)(4) (relating to Control Requirements). Where the requirements of 30 TAC Chapter 115, Subchapter F contain multiple compliance options, the permit holder shall keep records of when each compliance option was used.
  - (iv) Title 30 TAC § 115.542(b) - (d), (relating to Control Requirements)
  - (v) Title 30 TAC § 115.543 (relating to Alternate Control Requirements)
  - (vi) Title 30 TAC § 115.544(a)(1) and (a)(2) (relating to Inspection, Monitoring, and Testing Requirements), for inspections
  - (vii) Title 30 TAC § 115.544(b) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring
  - (viii) Title 30 TAC § 115.544(b)(1) and (b)(2) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring of control devices
  - (ix) Title 30 TAC § 115.544(b)(2)(A) - (J) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring (as appropriate to the control device)
  - (x) Title 30 TAC § 115.544(b)(3), (b)(4) and (b)(6) (relating to Inspection, Monitoring, and Testing Requirements), for VOC concentration or lower explosive limit threshold monitoring
  - (xi) Title 30 TAC § 115.544(c), and (c)(1) - (c)(3) (relating to Inspection, Monitoring, and Testing Requirements), for testing of control devices used to comply with 30 TAC § 115.542(a)(1)
  - (xii) Title 30 TAC § 115.545(1) - (7), (9) - (11) and (13) (relating to Approved Test Methods)
  - (xiii) Title 30 TAC § 115.546(a), (a)(1) and (a)(3) (relating to Recordkeeping and Notification Requirements), for recordkeeping
  - (xiv) Title 30 TAC § 115.546(a)(2) and (a)(2)(A) - (J) (relating to Recordkeeping and Notification Requirements), for recordkeeping (as appropriate to the control device)
  - (xv) Title 30 TAC § 115.546(a)(4) (relating to Recordkeeping and Notification Requirements), for recordkeeping of testing of control devices used to comply with 30 TAC § 115.542(a)(1)
  - (xvi) Title 30 TAC § 115.547(4) (relating to Exemptions)

6. The permit holder shall comply with the requirements of 30 TAC Chapter 113, Subchapter C, § 113.100 for units subject to any subpart of 40 CFR Part 63, unless otherwise stated in the applicable subpart.

#### **Additional Monitoring Requirements**

7. The permit holder shall comply with the periodic monitoring requirements as specified in the attached "Periodic Monitoring Summary" upon issuance of the permit. Except for, as applicable, monitoring malfunctions, associated repairs, and required quality assurance or control activities (including, as applicable, calibration checks and required zero and span adjustments), the permit holder shall conduct all monitoring in continuous operation (or shall collect data at all required intervals) at all times that the pollutant-specific emissions unit is operating. The permit holder may elect to collect monitoring data on a more frequent basis and average the data, consistent with the averaging time or minimum frequency specified in the "Periodic Monitoring Summary," for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular instances to avoid reporting deviations. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).

#### **New Source Review Authorization Requirements**

8. Permit holder shall comply with the requirements of New Source Review authorizations issued or claimed by the permit holder for the permitted area, including permits, permits by rule, standard permits, flexible permits, special permits, permits for existing facilities including Voluntary Emissions Reduction Permits and Electric Generating Facility Permits issued under 30 TAC Chapter 116, Subchapter I, or special exemptions referenced in the New Source Review Authorization References attachment. These requirements:
  - A. Are incorporated by reference into this permit as applicable requirements
  - B. Shall be located with this operating permit
  - C. Are not eligible for a permit shield
9. The permit holder shall comply with the general requirements of 30 TAC Chapter 106, Subchapter A or the general requirements, if any, in effect at the time of the claim of any PBR.
10. The permit holder shall maintain records to demonstrate compliance with any emission limitation or standard that is specified in a permit by rule (PBR) or Standard Permit listed in the New Source Review Authorizations attachment. The records shall yield reliable data from the relevant time period that are representative of the emission unit's compliance with the PBR or Standard Permit. These records may include, but are not limited to, production capacity and throughput, hours of operation, safety data sheets (SDS), chemical composition of raw materials, speciation of air contaminant data, engineering calculations, maintenance records, fugitive data, performance tests, capture/control device efficiencies, direct pollutant monitoring (CEMS, COMS, or PEMS), or control device parametric monitoring. These records shall be made readily accessible and available as required by 30 TAC § 122.144. Any monitoring or recordkeeping data indicating noncompliance with the PBR or Standard Permit shall be considered and reported as a deviation according to 30 TAC § 122.145 (Reporting Terms and Conditions).

#### **Compliance Requirements**

11. The permit holder shall certify compliance in accordance with 30 TAC § 122.146. The permit holder shall comply with 30 TAC § 122.146 using at a minimum, but not limited to, the continuous or intermittent compliance method data from monitoring, recordkeeping, reporting, or testing

required by the permit and any other credible evidence or information. The certification period may not exceed 12 months and the certification must be submitted within 30 days after the end of the period being certified.

12. Permit holder shall comply with the following 30 TAC Chapter 117 requirements:
  - A. The permit holder shall comply with the compliance schedules and submit written notification to the TCEQ Executive Director as required in 30 TAC Chapter 117, Subchapter H, Division 1:
    - (i) For sources in the Beaumont-Port Arthur Nonattainment area, 30 TAC § 117.9000
13. Use of Emission Credits to comply with applicable requirements:
  - A. Unless otherwise prohibited, the permit holder may use emission credits to comply with the following applicable requirements listed elsewhere in this permit:
    - (i) Title 30 TAC Chapter 115
    - (ii) Title 30 TAC Chapter 117
    - (iii) Offsets for Title 30 TAC Chapter 116
  - B. The permit holder shall comply with the following requirements in order to use the emission credits to comply with the applicable requirements:
    - (i) The permit holder must notify the TCEQ according to 30 TAC § 101.306(c)-(d)
    - (ii) The emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 1
    - (iii) The executive director has approved the use of the credit according to 30 TAC § 101.306(c)-(d)
    - (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.302(g) and 30 TAC Chapter 122
    - (v) Title 30 TAC § 101.305 (relating to Emission Reductions Achieved Outside the United States)
14. Use of Discrete Emission Credits to comply with the applicable requirements:
  - A. Unless otherwise prohibited, the permit holder may use discrete emission credits to comply with the following applicable requirements listed elsewhere in this permit:
    - (i) Title 30 TAC Chapter 115
    - (ii) Title 30 TAC Chapter 117
    - (iii) If applicable, offsets for Title 30 TAC Chapter 116
    - (iv) Temporarily exceed state NSR permit allowables

- B. The permit holder shall comply with the following requirements in order to use the credit to comply with the applicable requirements:
- (i) The permit holder must notify the TCEQ according to 30 TAC § 101.376(d)
  - (ii) The discrete emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 4
  - (iii) The executive director has approved the use of the discrete emission credits according to 30 TAC § 101.376(d)(1)(A)
  - (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.372(h) and 30 TAC Chapter 122
  - (v) Title 30 TAC § 101.375 (relating to Emission Reductions Achieved Outside the United States)

### **Risk Management Plan**

15. For processes subject to 40 CFR Part 68 and specified in 40 CFR § 68.10, the permit holder shall comply with the requirements of the Accidental Release Prevention Provisions in 40 CFR Part 68. The permit holder shall submit to the appropriate agency either a compliance schedule for meeting the requirements of 40 CFR Part 68 by the date provided in 40 CFR § 68.10(a), or as part of the compliance certification submitted under this permit, a certification statement that the source is in compliance with all requirements of 40 CFR Part 68, including the registration and submission of a risk management plan.

### **Protection of Stratospheric Ozone**

16. Permit holders at a site subject to Title VI of the FCAA Amendments shall meet the following requirements for protection of stratospheric ozone:
- A. Any on site servicing, maintenance, and repair on refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants or non-exempt substitutes shall be conducted in accordance with 40 CFR Part 82, Subpart F. Permit holders shall ensure that repairs on or refrigerant removal from refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants are performed only by properly certified technicians using certified equipment. Records shall be maintained as required by 40 CFR Part 82, Subpart F.
  - B. The permit holder shall comply with 40 CFR Part 82, Subpart A for controlling the production, transformation, destruction, export or import of a controlled (ozone-depleting) substance or product as specified in 40 CFR § 82.1 - § 82.13 and the applicable Part 82 Appendices.
  - C. The permit holder shall comply with 40 CFR Part 82, Subpart H related to Halon Emissions Reduction requirements as specified in 40 CFR § 82.250 - § 82.270 and the applicable Part 82 Appendices.
  - D. The permit holder shall comply with 40 CFR Part 82, Subpart A, § 82.13 related to recordkeeping and reporting requirements for the production and consumption of ozone depleting substances.



**Permit Location**

17. The permit holder shall maintain a copy of this permit and records related to requirements listed in this permit on site.

**Permit Shield (30 TAC § 122.148)**

18. A permit shield is granted for the emission units, groups, or processes specified in the attached "Permit Shield." Compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements listed in the attachment "Permit Shield." Permit shield provisions shall not be modified by the executive director until notification is provided to the permit holder. No later than 90 days after notification of a change in a determination made by the executive director, the permit holder shall apply for the appropriate permit revision to reflect the new determination. Provisional terms are not eligible for this permit shield. Any term or condition, under a permit shield, shall not be protected by the permit shield if it is replaced by a provisional term or condition or the basis of the term and condition changes.

## **Attachments**

**Applicable Requirements Summary**

**Additional Monitoring Requirements**

**Permit Shield**

**New Source Review Authorization References**

### **Applicable Requirements Summary**

<b>Unit Summary .....</b>	<b>14</b>
<b>Applicable Requirements Summary .....</b>	<b>21</b>

Note: A “none” entry may be noted for some emission sources in this permit’s “Applicable Requirements Summary” under the heading of “Monitoring and Testing Requirements” and/or “Recordkeeping Requirements” and/or “Reporting Requirements.” Such a notation indicates that there are no requirements for the indicated emission source as identified under the respective column heading(s) for the stated portion of the regulation when the emission source is operating under the conditions of the specified SOP Index Number. However, other relevant requirements pursuant to 30 TAC Chapter 122 including Recordkeeping Terms and Conditions (30 TAC § 122.144), Reporting Terms and Conditions (30 TAC § 122.145), and Compliance Certification Terms and Conditions (30 TAC § 122.146) continue to apply.

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
E3FE353	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-22	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
E3FE353	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63PPP	40 CFR Part 63, Subpart PPP	No changing attributes.
E3FE355	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-22	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
E3FE355	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63PPP	40 CFR Part 63, Subpart PPP	No changing attributes.
E3FE356	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-22	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
E3FE356	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63PPP	40 CFR Part 63, Subpart PPP	No changing attributes.
E3FUG	FUGITIVE EMISSION UNITS	N/A	R5352-ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
E3LROSCW	LOADING/UNLOADIN G OPERATIONS	N/A	R5211-018	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
E3LRSICW	LOADING/UNLOADIN G OPERATIONS	N/A	R5211-018	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
E3NSCRB	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R1111-01	30 TAC Chapter 111, Visible Emissions	No changing attributes.
E3TE3381	STORAGE TANKS/VESSELS	N/A	R5112-00a	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
E3TE3386	STORAGE TANKS/VESSELS	N/A	R5112-00c	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
E3TE3386	STORAGE TANKS/VESSELS	N/A	63PPP	40 CFR Part 63, Subpart PPP	No changing attributes.
E3TE3387	STORAGE TANKS/VESSELS	N/A	R5112-00a	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
E3TE3388	STORAGE TANKS/VESSELS	N/A	R5112-00a	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
E3TE3388	STORAGE TANKS/VESSELS	N/A	63PPP	40 CFR Part 63, Subpart PPP	No changing attributes.
E3TE3389	STORAGE TANKS/VESSELS	N/A	R5112-00c	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
E3TE357	STORAGE TANKS/VESSELS	N/A	R5112-00c	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
E6FUG	FUGITIVE EMISSION UNITS	N/A	R5352-ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
E6LR0SCW	LOADING/UNLOADIN G OPERATIONS	N/A	R5211-018	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
E6LR0SPC	LOADING/UNLOADIN G OPERATIONS	N/A	R5211-018	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
E6LR0SPW	LOADING/UNLOADIN G OPERATIONS	N/A	R5211-018	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
E6NSCRB	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R1111-01	30 TAC Chapter 111, Visible Emissions	No changing attributes.
E6SCRBTk	STORAGE TANKS/VESSELS	N/A	R5112-00a	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
E6TE614	STORAGE TANKS/VESSELS	N/A	R5112-00a	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
E6TE614	STORAGE TANKS/VESSELS	N/A	63PPP	40 CFR Part 63, Subpart PPP	No changing attributes.
E6TE6212	STORAGE TANKS/VESSELS	N/A	R5112-00g	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
E6TE6212	STORAGE TANKS/VESSELS	N/A	63PPP	40 CFR Part 63, Subpart PPP	No changing attributes.
E6TE6213	STORAGE TANKS/VESSELS	N/A	R5112-00a	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
E6TE6214	STORAGE TANKS/VESSELS	N/A	R115	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
E6TE628A	STORAGE TANKS/VESSELS	N/A	R5112-00g	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
E6TE628A	STORAGE TANKS/VESSELS	N/A	63PPP	40 CFR Part 63, Subpart PPP	No changing attributes.
E6TE628B	STORAGE TANKS/VESSELS	N/A	R5112-00g	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
E6TE628B	STORAGE TANKS/VESSELS	N/A	63PPP	40 CFR Part 63, Subpart PPP	No changing attributes.
E6TE632	STORAGE TANKS/VESSELS	N/A	R5112-00a	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
E6TE632	STORAGE TANKS/VESSELS	N/A	63PPP	40 CFR Part 63, Subpart PPP	No changing attributes.
E7RE9803	FLARES	N/A	R111	30 TAC Chapter 111, Visible Emissions	No changing attributes.
FUG63PPP	FUGITIVE EMISSION UNITS	N/A	63PPP	40 CFR Part 63, Subpart PPP	No changing attributes.
GRPE3TK1	STORAGE TANKS/VESSELS	E3TE3367, E3TE3368, E3TE3369, E3TE3370, E3TE3371, E3TE3385	R5112-00g	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRPE3TK1	STORAGE TANKS/VESSELS	E3TE3367, E3TE3368, E3TE3369, E3TE3370, E3TE3371, E3TE3385	63PPP	40 CFR Part 63, Subpart PPP	No changing attributes.
GRPE3TK2	STORAGE TANKS/VESSELS	E3TE312, E3TE3128, E3TE313, E3TE314, E3TE3147, E3TE3148, E3TE3149, E3TE315, E3TE3150, E3TE3151, E3TE3152, E3TE3153, E3TE3154, E3TE3155, E3TE3358, E3TE3360, E3TE3361, E3TE3363, E3TE3364, E3TE3377, E3TE3378, E3TE3379, E3TE3380, E3TE344, E3TE391, E3TE392, E3TE393, E3TE394, E3TE3358, E3TE3380	R5112-00a	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRPE3TK3	STORAGE TANKS/VESSELS	E3TE3357, E3TE3359, E3TE3362, E3TE3376, E3TE345, E3TE347	R5112-00c	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRPE3TK3	STORAGE	E3TE3357, E3TE3359,	63PPP	40 CFR Part 63, Subpart PPP	No changing attributes.

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	TANKS/VESSELS	E3TE3362, E3TE3376, E3TE345, E3TE347			
GRPE3TK4	STORAGE TANKS/VESSELS	E3TE3125, E3TE3374, E3TE3375, E3TE346, E3TE348	R5112-00g	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRPE3TK4	STORAGE TANKS/VESSELS	E3TE3125, E3TE3374, E3TE3375, E3TE346, E3TE348	63PPP	40 CFR Part 63, Subpart PPP	No changing attributes.
GRPE6PV1	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	E6FE61, E6FE62, E6FE624, E6FE63, E6FE64	R5121-20	30 TAC Chapter 115, Vent Gas Controls	Control Device Type = Smokeless flare
GRPE6PV1	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	E6FE61, E6FE62, E6FE624, E6FE63, E6FE64	R5121-22	30 TAC Chapter 115, Vent Gas Controls	Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.
GRPE6PV1	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	E6FE61, E6FE62, E6FE624, E6FE63, E6FE64	R5121-226	30 TAC Chapter 115, Vent Gas Controls	Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.
GRPE6PV1	EMISSION POINTS/STATIONARY	E6FE61, E6FE62, E6FE624, E6FE63, E6FE64	63PPP	40 CFR Part 63, Subpart PPP	No changing attributes.



### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	VENTS/PROCESS VENTS				
GRPE6TK1	STORAGE TANKS/VESSELS	E6TE633, E6TE634, E6TE635, E6TE640, E6TE641	R5112-00c	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRPE6TK1	STORAGE TANKS/VESSELS	E6TE633, E6TE634, E6TE635, E6TE640, E6TE641	63PPP	40 CFR Part 63, Subpart PPP	No changing attributes.
GRPE6TK2	STORAGE TANKS/VESSELS	E6TE636, E6TE637, E6TE638, E6TE639, E6TE651	R5112-00g	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRPE6TK2	STORAGE TANKS/VESSELS	E6TE636, E6TE637, E6TE638, E6TE639, E6TE651	63PPP	40 CFR Part 63, Subpart PPP	No changing attributes.
GRPE6TK3	STORAGE TANKS/VESSELS	E6TE61, E6TE610, E6TE611, E6TE62, E6TE63, E6TE64, E6TE65, E6TE66, E6TE67, E6TE68, E6TE69	R5112-00c	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRPE6TK3	STORAGE TANKS/VESSELS	E6TE61, E6TE610, E6TE611, E6TE62, E6TE63, E6TE64, E6TE65, E6TE66, E6TE67, E6TE68, E6TE69	63PPP	40 CFR Part 63, Subpart PPP	No changing attributes.
PROE3FE353	CHEMICAL MANUFACTURING PROCESS	N/A	R5160-01	30 TAC Chapter 115, Batch Processes	No changing attributes.
PROE3FE355	CHEMICAL MANUFACTURING PROCESS	N/A	R5160-01	30 TAC Chapter 115, Batch Processes	No changing attributes.
PROE3FE356	CHEMICAL MANUFACTURING PROCESS	N/A	R5160-01	30 TAC Chapter 115, Batch Processes	No changing attributes.
PROE6FE61	CHEMICAL MANUFACTURING PROCESS	N/A	R5160-01	30 TAC Chapter 115, Batch Processes	Control Device = Absorber.

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
PROE6FE61	CHEMICAL MANUFACTURING PROCESS	N/A	R5160-02	30 TAC Chapter 115, Batch Processes	Control Device = Flare.
PROE6FE62	CHEMICAL MANUFACTURING PROCESS	N/A	R5160-01	30 TAC Chapter 115, Batch Processes	Control Device = Absorber.
PROE6FE62	CHEMICAL MANUFACTURING PROCESS	N/A	R5160-02	30 TAC Chapter 115, Batch Processes	Control Device = Flare.
PROE6FE624	CHEMICAL MANUFACTURING PROCESS	N/A	R5160-01	30 TAC Chapter 115, Batch Processes	Control Device = Absorber.
PROE6FE624	CHEMICAL MANUFACTURING PROCESS	N/A	R5160-02	30 TAC Chapter 115, Batch Processes	Control Device = Flare.
PROE6FE63	CHEMICAL MANUFACTURING PROCESS	N/A	R5160-01	30 TAC Chapter 115, Batch Processes	Control Device = Absorber.
PROE6FE63	CHEMICAL MANUFACTURING PROCESS	N/A	R5160-02	30 TAC Chapter 115, Batch Processes	Control Device = Flare.
PROE6FE64	CHEMICAL MANUFACTURING PROCESS	N/A	R5160-01	30 TAC Chapter 115, Batch Processes	Control Device = Absorber.
PROE6FE64	CHEMICAL MANUFACTURING PROCESS	N/A	R5160-02	30 TAC Chapter 115, Batch Processes	Control Device = Flare.

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
E3FE353	EP	R5121-22	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(4)(A) [G]§ 115.122(a)(4) § 115.127(a)(4)	Any SOCMI reactor process or distillation operation that is designed and operated in a batch mode is exempt from the requirements of §115.121(a)(2)(A) of this title.	None	None	None
E3FE353	EU	63PPP	112(B)HAP	40 CFR Part 63, Subpart PPP	§ 63.1425(b)(2)(ii) § 63.1425(a) § 63.1425(b)	Owners and operators of all affected sources shall reduce the total epoxide emissions from the group of applicable process vents by an aggregated 98 percent.	§ 63.1426(a) § 63.1426(b)(3) § 63.1429(a)(2) § 63.1429(a)(4) § 63.1429(c) § 63.1429(d)	§ 63.1430(b)(1) § 63.1430(b)(2)(i) § 63.1430(c) § 63.1430(d)	§ 63.1430(g) § 63.1430(h)
E3FE355	EP	R5121-22	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(4)(A) [G]§ 115.122(a)(4) § 115.127(a)(4)	Any SOCMI reactor process or distillation operation that is designed and operated in a batch mode is exempt from the requirements of §115.121(a)(2)(A) of this title.	None	None	None
E3FE355	EU	63PPP	112(B)HAP	40 CFR Part 63, Subpart PPP	§ 63.1425(b)(2)(ii) § 63.1425(a) § 63.1425(b)	Owners and operators of all affected sources shall reduce the total epoxide emissions from the group of applicable process vents by an aggregated 98 percent.	§ 63.1426(a) § 63.1426(b)(3) § 63.1429(a)(2) § 63.1429(a)(4) § 63.1429(c) § 63.1429(d)	§ 63.1430(b)(1) § 63.1430(b)(2)(i) § 63.1430(c) § 63.1430(d)	§ 63.1430(g) § 63.1430(h)
E3FE356	EP	R5121-22	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(4)(A) [G]§ 115.122(a)(4) § 115.127(a)(4)	Any SOCMI reactor process or distillation operation that is designed and operated in a batch mode is exempt from the requirements of §115.121(a)(2)(A) of this	None	None	None

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						title.			
E3FE356	EU	63PPP	112(B)HAP	40 CFR Part 63, Subpart PPP	§ 63.1425(b)(2)(ii) § 63.1425(a) § 63.1425(b)	Owners and operators of all affected sources shall reduce the total epoxide emissions from the group of applicable process vents by an aggregated 98 percent.	§ 63.1426(a) § 63.1426(b)(3) § 63.1429(a)(2) § 63.1429(a)(4) § 63.1429(c) § 63.1429(d)	§ 63.1430(b)(1) § 63.1430(b)(2)(i) § 63.1430(c) § 63.1430(d)	§ 63.1430(g) § 63.1430(h)
E3FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight and components at a natural gas/gasoline processing operation that contact a process fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
E3FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
E3FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
E3FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
E3FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
E3FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
E3FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(C) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(8) § 115.357(8) § 115.358(c)(1) [G]§ 115.358(h)	No component shall be allowed to have a VOC leak, for more than 15 days, after discovery. If the owner or operator elects to use the alternative work practice in §115.358 of this title, any leak detected as defined in §115.358 of this title, including any leak detected using the alternative work practice on a component that is subject to the requirements of this division but not specifically selected for alternative work practice monitoring.	§ 115.354(1) § 115.354(11) § 115.354(13)(A) § 115.354(13)(B) § 115.354(13)(C) § 115.354(13)(D) § 115.354(13)(E) § 115.354(13)(F) § 115.354(4) § 115.354(5) § 115.354(9) [G]§ 115.355 § 115.358(c)(2) § 115.358(d) [G]§ 115.358(e) § 115.358(f)	§ 115.352(7) § 115.354(13)(D) § 115.354(13)(E) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) [G]§ 115.356(4) § 115.356(5)	[G]§ 115.358(g)
E3FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
E3FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2)	None

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(3) § 115.352(7)	screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5)	
E3FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(8) § 115.357(9)	No pressure relief valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
E3FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8) § 115.357(9)	No pressure relief valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
E3FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery	§ 115.352(1)(A) § 115.352(1)	No open-ended valves or lines shall be allowed to	§ 115.354(1) § 115.354(2)	§ 115.352(7) § 115.356	[G]§ 115.354(7)

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				& Petrochemicals	§ 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9)	have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	[G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	
E3FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	No open-ended valves or lines shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
E3FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1)	No valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight,	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)



### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(8) § 115.357(9)	smell, or sound.			
E3FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	No valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
E3FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(1) § 115.357(12) § 115.357(8)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
E3FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(1) § 115.357(12) § 115.357(8)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B)	None

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(8) § 115.357(12) § 115.357(8)	per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.357(1)	[G]§ 115.356(3)(C) § 115.356(5)	
E3FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(1) § 115.357(12) § 115.357(8)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
E3FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(1) § 115.357(12) § 115.357(8)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
E3FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1)	None

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(12) § 115.357(8)	which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(9) [G]§ 115.355 § 115.357(1)	[G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	
E3FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(3) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
E3FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
E3FUG	EU	R5352-	VOC	30 TAC Chapter	§ 115.352(1)(B)	No compressor seals	§ 115.354(1)	§ 115.352(7)	None

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		ALL		115, Pet. Refinery & Petrochemicals	§ 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	
E3FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
E3FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(7) § 115.357(4) § 115.357(8)	fluid based on sight, smell, or sound.			
E3FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
E3FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
E3LROSCW	EU	R5211-018	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(1) § 115.212(a)(2) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Vapor pressure (at land-based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						this division, except as specified.			
E3LRSICW	EU	R5211-018	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(1) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Vapor pressure (at land-based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified.	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None
E3NSCRB	EP	R1111-01	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(A) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 30% averaged over a six minute period.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
E3TE3381	EU	R5112-00a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
E3TE3386	EU	R5112-00c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
E3TE3386	EU	63PPP	112(B)HAP	40 CFR Part 63, Subpart PPP	§ 63.1432(a) § 63.119(a)(3)	For each storage vessel located at an affected source, the owner or operator shall comply with the HON storage vessel requirements of	None	§ 63.123(a) § 63.123(b) § 63.123(d)	§ 63.152(c)(4)(iii)

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§§63.119 through 63.123 and the HON leak inspection provisions in §63.148, with the differences noted in paragraphs (b) through (p) of this section, for the purposes of this subpart.			
E3TE3387	EU	R5112-00a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
E3TE3388	EU	R5112-00a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
E3TE3388	EU	63PPP	112(B)HAP	40 CFR Part 63, Subpart PPP	§ 63.1432(a) § 63.119(a)(3)	For each storage vessel located at an affected source, the owner or operator shall comply with the HON storage vessel requirements of §§63.119 through 63.123 and the HON leak inspection provisions in §63.148, with the differences noted in paragraphs (b) through (p) of this section, for the purposes of this subpart.	None	§ 63.123(a) § 63.123(b) § 63.123(d)	§ 63.152(c)(4)(iii)
E3TE3389	EU	R5112-00c	VOC	30 TAC Chapter	§ 115.111(a)(1)	Except as provided in §	[G]§ 115.117	§ 115.118(a)(1)	None

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Storage of VOCs		115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.		§ 115.118(a)(5) § 115.118(a)(7)	
E3TE357	EU	R5112-00c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
E6FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight and components at a natural gas/gasoline processing operation that contact a process fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
E6FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None



### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						operations are exempt from the requirements of this division except §115.356(3)(C) of this title.			
E6FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
E6FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
E6FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
E6FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
E6FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(C) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(8) § 115.357(8) § 115.358(c)(1) [G]§ 115.358(h)	No component shall be allowed to have a VOC leak, for more than 15 days, after discovery. If the owner or operator elects to use the alternative work practice in §115.358 of this title, any leak detected as defined in §115.358 of this title, including any leak detected using the alternative work practice on a component that is subject to the requirements of this division but not specifically selected for alternative work practice monitoring.	§ 115.354(1) § 115.354(11) § 115.354(13)(A) § 115.354(13)(B) § 115.354(13)(C) § 115.354(13)(D) § 115.354(13)(E) § 115.354(13)(F) § 115.354(4) § 115.354(5) § 115.354(9) [G]§ 115.355 § 115.358(c)(2) § 115.358(d) [G]§ 115.358(e) § 115.358(f)	§ 115.352(7) § 115.354(13)(D) § 115.354(13)(E) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) [G]§ 115.356(4) § 115.356(5)	[G]§ 115.358(g)
E6FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
E6FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5)	None
E6FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(8) § 115.357(9)	No pressure relief valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
E6FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(12)	No pressure relief valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(8) § 115.357(9)	exuding of process fluid based on sight, smell, or sound.			
E6FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9)	No open-ended valves or lines shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
E6FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	No open-ended valves or lines shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
E6FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(3)	No valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9)	per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.357(1)		
E6FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	No valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
E6FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(1) § 115.357(12) § 115.357(8)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
E6FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10)	No flanges or other connectors shall be allowed to have a VOC	§ 115.354(1) § 115.354(10) § 115.354(11)	§ 115.352(7) § 115.354(10) § 115.356	None

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(12) § 115.357(8)	leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	[G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	
E6FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(1) § 115.357(12) § 115.357(8)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
E6FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(1) § 115.357(12) § 115.357(12)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(8)				
E6FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(12) § 115.357(8)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
E6FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(3) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
E6FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane,	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8)	or the dripping or exuding of process fluid based on sight, smell, or sound.			
E6FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
E6FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
E6FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C)	None



### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8)	greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.		§ 115.356(5)	
E6FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
E6FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
E6LR0SCW	EU	R5211-018	VOC	30 TAC Chapter 115, Loading and	§ 115.217(a)(1) § 115.212(a)(2)	Vapor pressure (at land-based operations). All	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i)	§ 115.216 § 115.216(2)	None

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Unloading of VOC	§ 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	land-based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified.	§ 115.215 § 115.215(4)	§ 115.216(3)(B)	
E6LR0SPC	EU	R5211-018	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(1) § 115.212(a)(2) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Vapor pressure (at land-based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified.	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None
E6LR0SPW	EU	R5211-018	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(1) § 115.212(a)(2) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Vapor pressure (at land-based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified.	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None
E6NSCRB	EP	R1111-01	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(A) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 30% averaged over a six minute period.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
E6SCRBTk	EU	R5112-00a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
E6TE614	EU	R5112-00a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
E6TE614	EU	63PPP	112(B)HAP	40 CFR Part 63, Subpart PPP	§ 63.1432(a) § 63.119(a)(3)	For each storage vessel located at an affected source, the owner or operator shall comply with the HON storage vessel requirements of §§63.119 through 63.123 and the HON leak inspection provisions in §63.148, with the differences noted in paragraphs (b) through (p) of this section, for the purposes of this subpart.	None	§ 63.123(a) § 63.123(b) § 63.123(d)	§ 63.152(c)(4)(iii)
E6TE6212	EU	R5112-00g	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
E6TE6212	EU	63PPP	112(B)HAP	40 CFR Part 63, Subpart PPP	§ 63.1432(a) § 63.119(a)(3)	For each storage vessel located at an affected source, the owner or operator shall comply with the HON storage vessel requirements of §§63.119 through 63.123 and the HON leak inspection provisions in §63.148, with the	None	§ 63.123(a) § 63.123(b) § 63.123(d)	§ 63.152(c)(4)(iii)

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						differences noted in paragraphs (b) through (p) of this section, for the purposes of this subpart.			
E6TE6213	EU	R5112-00a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
E6TE6214	EU	R115	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
E6TE628A	EU	R5112-00g	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
E6TE628A	EU	63PPP	112(B)HAP	40 CFR Part 63, Subpart PPP	§ 63.1432(a) § 63.119(a)(3)	For each storage vessel located at an affected source, the owner or operator shall comply with the HON storage vessel requirements of §§63.119 through 63.123 and the HON leak inspection provisions in §63.148, with the differences noted in paragraphs (b) through	None	§ 63.123(a) § 63.123(b) § 63.123(d)	§ 63.152(c)(4)(iii)

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						(p) of this section, for the purposes of this subpart.			
E6TE628B	EU	R5112-00g	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
E6TE628B	EU	63PPP	112(B)HAP	40 CFR Part 63, Subpart PPP	§ 63.1432(a) § 63.119(a)(3)	For each storage vessel located at an affected source, the owner or operator shall comply with the HON storage vessel requirements of §§63.119 through 63.123 and the HON leak inspection provisions in §63.148, with the differences noted in paragraphs (b) through (p) of this section, for the purposes of this subpart.	None	§ 63.123(a) § 63.123(b) § 63.123(d)	§ 63.152(c)(4)(iii)
E6TE632	EU	R5112-00a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
E6TE632	EU	63PPP	112(B)HAP	40 CFR Part 63, Subpart PPP	§ 63.1532(a) § 63.119(a)(3)	For each storage vessel located at an affected source, the owner or operator shall comply with the HON storage vessel requirements of §§63.119 through 63.123	None	§ 63.123(a) § 63.123(b) § 63.123(d)	§ 63.152(c)(4)(iii)

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						and the HON leak inspection provisions in §63.148, with the differences noted in paragraphs (b) through (p) of this section, for the purposes of this subpart.			
E7RE9803	EU	R111	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for upset emissions as provided in §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
FUG63PPP	EU	63PPP	112(B) HAPS	40 CFR Part 63, Subpart PPP	§ 63.1420 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart PPP	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart PPP	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart PPP	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart PPP	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart PPP
GRPE3TK1	EU	R5112-00g	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRPE3TK1	EU	63PPP	112(B) HAPS	40 CFR Part 63, Subpart PPP	§ 63.1432(a) § 63.119(a)(3)	For each storage vessel located at an affected source, the owner or operator shall comply with the HON storage vessel requirements of	None	§ 63.123(a) § 63.123(b) § 63.123(d)	§ 63.1152(c)(4)(iii)

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§§63.119 through 63.123 and the HON leak inspection provisions in §63.148, with the differences noted in paragraphs (b) through (p) of this section, for the purposes of this subpart.			
GRPE3TK2	EU	R5112-00a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRPE3TK3	EU	R5112-00c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRPE3TK3	EU	63PPP	112(B)HAP	40 CFR Part 63, Subpart PPP	§ 63.1432(a) § 63.119(a)(3)	For each storage vessel located at an affected source, the owner or operator shall comply with the HON storage vessel requirements of §§63.119 through 63.123 and the HON leak inspection provisions in §63.148, with the differences noted in paragraphs (b) through (p) of this section, for the purposes of this subpart.	None	§ 63.123(a) § 63.123(b) § 63.123(d)	§ 63.152(c)(4)(iii)
GRPE3TK4	EU	R5112-00g	VOC	30 TAC Chapter	§ 115.111(a)(1)	Except as provided in §	[G]§ 115.117	§ 115.118(a)(1)	None

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Storage of VOCs		115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.		§ 115.118(a)(5) § 115.118(a)(7)	
GRPE3TK4	EU	63PPP	112(B)HAP	40 CFR Part 63, Subpart PPP	§ 63.1432(a) § 63.119(a)(3)	For each storage vessel located at an affected source, the owner or operator shall comply with the HON storage vessel requirements of §§63.119 through 63.123 and the HON leak inspection provisions in §63.148, with the differences noted in paragraphs (b) through (p) of this section, for the purposes of this subpart.	None	§ 63.123(a) § 63.123(b) § 63.123(d)	§ 63.152(c)(4)(iii)
GRPE6PV1	EP	R5121-20	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(4)(A) [G]§ 115.122(a)(4) § 115.127(a)(4)	Any SOCMI reactor process or distillation operation that is designed and operated in a batch mode is exempt from the requirements of §115.121(a)(2)(A) of this title.	None	None	None
GRPE6PV1	EP	R5121-22	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(4)(A) [G]§ 115.122(a)(4) § 115.127(a)(4)	Any SOCMI reactor process or distillation operation that is designed and operated in a batch mode is exempt from the requirements of §115.121(a)(2)(A) of this title.	None	None	None
GRPE6PV1	EP	R5121-226	VOC	30 TAC Chapter	§ 115.127(a)(4)(A)	Any SOCMI reactor	None	None	None



### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Vent Gas Controls	[G]§ 115.122(a)(4) § 115.127(a)(4)	process or distillation operation that is designed and operated in a batch mode is exempt from the requirements of §115.121(a)(2)(A) of this title.			
GRPE6PV1	EU	63PPP	112(B)HAP	40 CFR Part 63, Subpart PPP	§ 63.1425(b)(2)(ii) § 63.1425(a) § 63.1425(b)	Owners and operators of all affected sources shall reduce the total epoxide emissions from the group of applicable process vents by an aggregated 98 percent.	§ 63.1426(a) § 63.1426(b)(3) § 63.1429(a)(2) § 63.1429(a)(4) § 63.1429(c) § 63.1429(d)	§ 63.1430(b)(1) § 63.1430(b)(2)(i) § 63.1430(c) § 63.1430(d)	§ 63.1430(g) § 63.1430(h)
GRPE6TK1	EU	R5112-00c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRPE6TK1	EU	63PPP	112(B)HAP	40 CFR Part 63, Subpart PPP	§ 63.1432(a) § 63.119(a)(3)	For each storage vessel located at an affected source, the owner or operator shall comply with the HON storage vessel requirements of §§63.119 through 63.123 and the HON leak inspection provisions in §63.148, with the differences noted in paragraphs (b) through (p) of this section, for the purposes of this subpart.	None	§ 63.123(a) § 63.123(b) § 63.123(d)	§ 63.152(c)(4)(iii)
GRPE6TK2	EU	R5112-00g	VOC	30 TAC Chapter 115, Storage of	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5)	None

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				VOCs		storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.		§ 115.118(a)(7)	
GRPE6TK2	EU	63PPP	112(B)HAP	40 CFR Part 63, Subpart PPP	§ 63.1432(a) § 63.119(a)(3)	For each storage vessel located at an affected source, the owner or operator shall comply with the HON storage vessel requirements of §§63.119 through 63.123 and the HON leak inspection provisions in §63.148, with the differences noted in paragraphs (b) through (p) of this section, for the purposes of this subpart.	None	§ 63.123(a) § 63.123(b) § 63.123(d)	§ 63.152(c)(4)(iii)
GRPE6TK3	EU	R5112-00c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRPE6TK3	EU	63PPP	112(B)HAP	40 CFR Part 63, Subpart PPP	§ 63.1432(a) § 63.119(a)(3)	For each storage vessel located at an affected source, the owner or operator shall comply with the HON storage vessel requirements of §§63.119 through 63.123 and the HON leak inspection provisions in §63.148, with the differences noted in paragraphs (b) through	None	§ 63.123(a) § 63.123(b) § 63.123(d)	§ 63.152(c)(4)(iii)

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						(p) of this section, for the purposes of this subpart.			
PROE3FE353	EU	R5160-01	VOC	30 TAC Chapter 115, Batch Processes	§ 115.162(1) § 115.162(1)(A) § 115.162(1)(B) § 115.162(1)(C) § 115.162(2) § 115.162(2)(B) § 115.162(2)(D) § 115.162(2)(E)	The mass emission rate from individual process vents or for process vent streams in aggregate within a batch process shall be reduced by 90% if the actual average flow rate value is below the flow rate value calculated using the applicable RACT equation.	§ 115.164(1) § 115.164(2) § 115.165(1) § 115.165(2) [G]§ 115.165(2)(A) [G]§ 115.165(2)(B) § 115.166 § 115.166(1) § 115.166(1)(A) § 115.166(1)(A)(iii) § 115.166(1)(A)(iii)(I) § 115.166(1)(A)(iii)(II) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(C)(i) § 115.166(3)(C)(iv)	§ 115.166 § 115.166(1) § 115.166(1)(A) § 115.166(1)(A)(iii) § 115.166(1)(A)(iii)(I) § 115.166(1)(A)(iii)(II) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(C)(i) § 115.166(3)(C)(iv)	None
PROE3FE355	EU	R5160-01	VOC	30 TAC Chapter 115, Batch Processes	§ 115.162(1) § 115.162(1)(A) § 115.162(1)(B) § 115.162(1)(C) § 115.162(2) § 115.162(2)(B) § 115.162(2)(D) § 115.162(2)(E)	The mass emission rate from individual process vents or for process vent streams in aggregate within a batch process shall be reduced by 90% if the actual average flow rate value is below the flow rate value calculated using the applicable RACT equation.	§ 115.164(1) § 115.164(2) § 115.165(1) § 115.165(2) [G]§ 115.165(2)(A) [G]§ 115.165(2)(B) § 115.166 § 115.166(1) § 115.166(1)(A) § 115.166(1)(A)(iii) § 115.166(1)(A)(iii)(I) § 115.166(1)(A)(iii)(II) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(C)(i) § 115.166(3)(C)(iv)	§ 115.166 § 115.166(1) § 115.166(1)(A) § 115.166(1)(A)(iii) § 115.166(1)(A)(iii)(I) § 115.166(1)(A)(iii)(II) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(C)(i) § 115.166(3)(C)(iv)	None
PROE3FE356	EU	R5160-01	VOC	30 TAC Chapter 115, Batch Processes	§ 115.162(1) § 115.162(1)(A) § 115.162(1)(B) § 115.162(1)(C)	The mass emission rate from individual process vents or for process vent streams in aggregate	§ 115.164(1) § 115.164(2) § 115.165(1) § 115.165(2)	§ 115.166 § 115.166(1) § 115.166(1)(A) § 115.166(1)(A)(iii)	None

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.162(2) § 115.162(2)(B) § 115.162(2)(D) § 115.162(2)(E)	within a batch process shall be reduced by 90% if the actual average flow rate value is below the flow rate value calculated using the applicable RACT equation.	[G]§ 115.165(2)(A) [G]§ 115.165(2)(B) § 115.166 § 115.166(1) § 115.166(1)(A) § 115.166(1)(A)(iii) § 115.166(1)(A)(iii)(I) § 115.166(1)(A)(iii)(II) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(C)(i) § 115.166(3)(C)(iv)	§ 115.166(1)(A)(iii)(I) § 115.166(1)(A)(iii)(II) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(C)(i) § 115.166(3)(C)(iv)	
PROE6FE61	EU	R5160-01	VOC	30 TAC Chapter 115, Batch Processes	§ 115.162(1) § 115.162(1)(A) § 115.162(1)(B) § 115.162(1)(C) § 115.162(2) § 115.162(2)(B) § 115.162(2)(D) § 115.162(2)(E)	The mass emission rate from individual process vents or for process vent streams in aggregate within a batch process shall be reduced by 90% if the actual average flow rate value is below the flow rate value calculated using the applicable RACT equation.	§ 115.164(1) § 115.164(2) § 115.165(1) § 115.165(2) [G]§ 115.165(2)(A) [G]§ 115.165(2)(B) § 115.166 § 115.166(1) § 115.166(1)(A) § 115.166(1)(A)(iii) § 115.166(1)(A)(iii)(I) § 115.166(1)(A)(iii)(II) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(C)(i) § 115.166(3)(C)(iv)	§ 115.166 § 115.166(1) § 115.166(1)(A) § 115.166(1)(A)(iii) § 115.166(1)(A)(iii)(I) § 115.166(1)(A)(iii)(II) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(C)(i) § 115.166(3)(C)(iv)	None
PROE6FE61	EU	R5160-02	VOC	30 TAC Chapter 115, Batch Processes	§ 115.162(1) § 115.162(1)(A) § 115.162(1)(B) § 115.162(1)(C) § 115.162(2) § 115.162(2)(B) § 115.162(2)(D) § 115.162(2)(E) § 60.18(b)	The mass emission rate from individual process vents or for process vent streams in aggregate within a batch process shall be reduced by 90% if the actual average flow rate value is below the flow rate value calculated using the applicable	§ 115.164(1) § 115.164(2) § 115.165(2)(C)(i) § 115.165(2)(C)(iii) § 115.165(2)(D) § 115.165(2)(E) § 115.166 § 115.166(1) § 115.166(1)(B) [G]§ 115.166(2)	§ 115.166 § 115.166(1) § 115.166(1)(B) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(B)	None

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						RACT equation.	§ 115.166(3) § 115.166(3)(B)		
PROE6FE62	EU	R5160-01	VOC	30 TAC Chapter 115, Batch Processes	§ 115.162(1) § 115.162(1)(A) § 115.162(1)(B) § 115.162(1)(C) § 115.162(2) § 115.162(2)(B) § 115.162(2)(D) § 115.162(2)(E)	The mass emission rate from individual process vents or for process vent streams in aggregate within a batch process shall be reduced by 90% if the actual average flow rate value is below the flow rate value calculated using the applicable RACT equation.	§ 115.164(1) § 115.164(2) § 115.165(1) § 115.165(2) [G]§ 115.165(2)(A) [G]§ 115.165(2)(B) § 115.166 § 115.166(1) § 115.166(1)(A) § 115.166(1)(A)(iii) § 115.166(1)(A)(iii)(I) § 115.166(1)(A)(iii)(II) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(C)(i) § 115.166(3)(C)(iv)	§ 115.166 § 115.166(1) § 115.166(1)(A) § 115.166(1)(A)(iii) § 115.166(1)(A)(iii)(I) § 115.166(1)(A)(iii)(II) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(C)(i) § 115.166(3)(C)(iv)	None
PROE6FE62	EU	R5160-02	VOC	30 TAC Chapter 115, Batch Processes	§ 115.162(1) § 115.162(1)(A) § 115.162(1)(B) § 115.162(1)(C) § 115.162(2) § 115.162(2)(B) § 115.162(2)(D) § 115.162(2)(E) § 60.18(b)	The mass emission rate from individual process vents or for process vent streams in aggregate within a batch process shall be reduced by 90% if the actual average flow rate value is below the flow rate value calculated using the applicable RACT equation.	§ 115.164(1) § 115.164(2) § 115.165(2)(C)(i) § 115.165(2)(C)(iii) § 115.165(2)(D) § 115.165(2)(E) § 115.166 § 115.166(1) § 115.166(1)(B) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(B)	§ 115.166 § 115.166(1) § 115.166(1)(B) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(B)	None
PROE6FE624	EU	R5160-01	VOC	30 TAC Chapter 115, Batch Processes	§ 115.162(1) § 115.162(1)(A) § 115.162(1)(B) § 115.162(1)(C) § 115.162(2) § 115.162(2)(B) § 115.162(2)(D) § 115.162(2)(E)	The mass emission rate from individual process vents or for process vent streams in aggregate within a batch process shall be reduced by 90% if the actual average flow rate value is below the	§ 115.164(1) § 115.164(2) § 115.165(1) § 115.165(2) [G]§ 115.165(2)(A) [G]§ 115.165(2)(B) § 115.166 § 115.166(1)	§ 115.166 § 115.166(1) § 115.166(1)(A) § 115.166(1)(A)(iii) § 115.166(1)(A)(iii)(I) § 115.166(1)(A)(iii)(II) [G]§ 115.166(2) § 115.166(3)	None

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						flow rate value calculated using the applicable RACT equation.	§ 115.166(1)(A) § 115.166(1)(A)(iii) § 115.166(1)(A)(iii)(I) § 115.166(1)(A)(iii)(II) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(C)(i) § 115.166(3)(C)(iv)	§ 115.166(3)(C)(i) § 115.166(3)(C)(iv)	
PROE6FE624	EU	R5160-02	VOC	30 TAC Chapter 115, Batch Processes	§ 115.162(1) § 115.162(1)(A) § 115.162(1)(B) § 115.162(1)(C) § 115.162(2) § 115.162(2)(B) § 115.162(2)(D) § 115.162(2)(E) § 60.18(b)	The mass emission rate from individual process vents or for process vent streams in aggregate within a batch process shall be reduced by 90% if the actual average flow rate value is below the flow rate value calculated using the applicable RACT equation.	§ 115.164(1) § 115.164(2) § 115.165(2)(C)(i) § 115.165(2)(C)(iii) § 115.165(2)(D) § 115.165(2)(E) § 115.166 § 115.166(1) § 115.166(1)(B) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(B)	§ 115.166 § 115.166(1) § 115.166(1)(B) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(B)	None
PROE6FE63	EU	R5160-01	VOC	30 TAC Chapter 115, Batch Processes	§ 115.162(1) § 115.162(1)(A) § 115.162(1)(B) § 115.162(1)(C) § 115.162(2) § 115.162(2)(B) § 115.162(2)(D) § 115.162(2)(E)	The mass emission rate from individual process vents or for process vent streams in aggregate within a batch process shall be reduced by 90% if the actual average flow rate value is below the flow rate value calculated using the applicable RACT equation.	§ 115.164(1) § 115.164(2) § 115.165(1) § 115.165(2) [G]§ 115.165(2)(A) [G]§ 115.165(2)(B) § 115.166 § 115.166(1) § 115.166(1)(A) § 115.166(1)(A)(iii) § 115.166(1)(A)(iii)(I) § 115.166(1)(A)(iii)(II) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(C)(i) § 115.166(3)(C)(iv)	§ 115.166 § 115.166(1) § 115.166(1)(A) § 115.166(1)(A)(iii) § 115.166(1)(A)(iii)(I) § 115.166(1)(A)(iii)(II) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(C)(i) § 115.166(3)(C)(iv)	None
PROE6FE63	EU	R5160-02	VOC	30 TAC Chapter 115, Batch	§ 115.162(1) § 115.162(1)(A)	The mass emission rate from individual process	§ 115.164(1) § 115.164(2)	§ 115.166 § 115.166(1)	None

### Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Processes	§ 115.162(1)(B) § 115.162(1)(C) § 115.162(2) § 115.162(2)(B) § 115.162(2)(D) § 115.162(2)(E) § 60.18(b)	vents or for process vent streams in aggregate within a batch process shall be reduced by 90% if the actual average flow rate value is below the flow rate value calculated using the applicable RACT equation.	§ 115.165(2)(C)(i) § 115.165(2)(C)(iii) § 115.165(2)(D) § 115.165(2)(E) § 115.166 § 115.166(1) § 115.166(1)(B) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(B)	§ 115.166(1)(B) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(B)	
PROE6FE64	EU	R5160-01	VOC	30 TAC Chapter 115, Batch Processes	§ 115.162(1) § 115.162(1)(A) § 115.162(1)(B) § 115.162(1)(C) § 115.162(2) § 115.162(2)(B) § 115.162(2)(D) § 115.162(2)(E)	The mass emission rate from individual process vents or for process vent streams in aggregate within a batch process shall be reduced by 90% if the actual average flow rate value is below the flow rate value calculated using the applicable RACT equation.	§ 115.164(1) § 115.164(2) § 115.165(1) § 115.165(2) [G]§ 115.165(2)(A) [G]§ 115.165(2)(B) § 115.166 § 115.166(1) § 115.166(1)(A) § 115.166(1)(A)(iii) § 115.166(1)(A)(iii)(I) § 115.166(1)(A)(iii)(II) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(C)(i) § 115.166(3)(C)(iv)	§ 115.166 § 115.166(1) § 115.166(1)(A) § 115.166(1)(A)(iii) § 115.166(1)(A)(iii)(I) § 115.166(1)(A)(iii)(II) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(C)(i) § 115.166(3)(C)(iv)	None
PROE6FE64	EU	R5160-02	VOC	30 TAC Chapter 115, Batch Processes	§ 115.162(1) § 115.162(1)(A) § 115.162(1)(B) § 115.162(1)(C) § 115.162(2) § 115.162(2)(B) § 115.162(2)(D) § 115.162(2)(E) § 60.18(b)	The mass emission rate from individual process vents or for process vent streams in aggregate within a batch process shall be reduced by 90% if the actual average flow rate value is below the flow rate value calculated using the applicable RACT equation.	§ 115.164(1) § 115.164(2) § 115.165(2)(C)(i) § 115.165(2)(C)(iii) § 115.165(2)(D) § 115.165(2)(E) § 115.166 § 115.166(1) § 115.166(1)(B) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(B)	§ 115.166 § 115.166(1) § 115.166(1)(B) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(B)	None

**Additional Monitoring Requirements**

**Periodic Monitoring Summary ..... 59**



### Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: E3NSCRB	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Opacity of more than 20% will be considered a deviation.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>If visible emissions are observed, the permit holder shall report a deviation. As an alternative, the permit holder may determine the opacity consistent with Test Method 9, as soon as practicable, but no later than 24 hours after observing visible emissions. If a Test Method 9 is performed, the opacity limit is the corresponding opacity limit associated with the particulate matter standard in the underlying applicable requirement. If there is no corresponding opacity limit in the underlying applicable requirement, the maximum opacity will be established using the most recent performance test. If the result of the Test Method 9 is opacity above the corresponding opacity limit (associated with the particulate matter standard in the underlying applicable requirement or as identified as a result of a previous performance test to establish the maximum opacity limit), the permit holder shall report a deviation.</p>	

### Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: E6NSCRB	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-01
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: Opacity of more than 20% will be considered a deviation.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>If visible emissions are observed, the permit holder shall report a deviation. As an alternative, the permit holder may determine the opacity consistent with Test Method 9, as soon as practicable, but no later than 24 hours after observing visible emissions. If a Test Method 9 is performed, the opacity limit is the corresponding opacity limit associated with the particulate matter standard in the underlying applicable requirement. If there is no corresponding opacity limit in the underlying applicable requirement, the maximum opacity will be established using the most recent performance test. If the result of the Test Method 9 is opacity above the corresponding opacity limit (associated with the particulate matter standard in the underlying applicable requirement or as identified as a result of a previous performance test to establish the maximum opacity limit), the permit holder shall report a deviation.</p>	

**Permit Shield**

**Permit Shield ..... 62**

### Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
E3TE3388	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 40 cubic meters (10,567 gallons).
E6TE614	N/A	40 CFR Part 60, Subpart Kb	Tank stores VOC (but not petroleum or petroleum liquids), but was constructed before 7/23/84 and has not been modified later than 7/23/84.
E6TE6212	N/A	40 CFR Part 60, Subpart Kb	Tank stores VOC (but not petroleum or petroleum liquids), but was constructed before 7/23/84 and has not been modified later than 7/23/84.
E6TE628A	N/A	40 CFR Part 60, Subpart Kb	Tank stores VOC (but not petroleum or petroleum liquids), but was constructed before 7/23/84 and has not been modified later than 7/23/84.
E6TE628B	N/A	40 CFR Part 60, Subpart Kb	Tank stores VOC (but not petroleum or petroleum liquids), but was constructed before 7/23/84 and has not been modified later than 7/23/84.
E6TE632	N/A	40 CFR Part 60, Subpart Kb	Tank stores VOC (but not petroleum or petroleum liquids), but was constructed before 7/23/84 and has not been modified later than 7/23/84.
GRPE3TK2	E3TE312, E3TE3128, E3TE313, E3TE314, E3TE3147, E3TE3148, E3TE3149, E3TE315, E3TE3150, E3TE3151, E3TE3152, E3TE3153,	40 CFR Part 60, Subpart Kb	Tank stores VOC (but not petroleum or petroleum liquids), but was constructed before 7/23/84 and has not been modified later than 7/23/84.

### Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
	E3TE3154, E3TE3155, E3TE3358, E3TE3360, E3TE3361, E3TE3363, E3TE3364, E3TE3377, E3TE3378, E3TE3379, E3TE3380, E3TE344, E3TE391, E3TE392, E3TE393, E3TE394		
GRPE3TK4	E3TE3125, E3TE3374, E3TE3375, E3TE346, E3TE348	40 CFR Part 60, Subpart Kb	Tank stores VOC (but not petroleum or petroleum liquids), but was constructed before 7/23/84 and has not been modified later than 7/23/84.
GRPE6PV1	E6FE61, E6FE62, E6FE624, E6FE63, E6FE64	40 CFR Part 60, Subpart RRR	Reactor process is designed and operated as a batch operation
GRPE6TK3	E6TE61, E6TE610, E6TE611, E6TE62, E6TE63, E6TE64, E6TE65, E6TE66, E6TE67, E6TE68, E6TE69	40 CFR Part 60, Subpart Kb	Tank stores VOC (but not petroleum or petroleum liquids), but was constructed before 7/23/84 and has not been modified later than 7/23/84.
UEUL30	N/A	40 CFR Part 63, Subpart Q	Cooling tower is not operated with chromium-based water treatment chemicals

**New Source Review Authorization References**

<b>New Source Review Authorization References .....</b>	<b>65</b>
<b>New Source Review Authorization References by Emission Unit .....</b>	<b>66</b>

### New Source Review Authorization References

The New Source Review authorizations listed in the table below are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.	
Authorization No.: 20134	Issuance Date: 02/11/2015
Permits By Rule (30 TAC Chapter 106) for the Application Area	
Number: 106.261	Version No./Date: 11/01/2003
Number: 106.262	Version No./Date: 11/01/2003
Number: 106.264	Version No./Date: 09/04/2000
Number: 106.472	Version No./Date: 09/04/2000

### New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
E3FE353	REACTOR	20134
E3FE355	REACTOR	20134
E3FE356	REACTOR	20134
E3FUG	E3 UNIT FUGITIVES	20134
E3LROSCW	RAILCAR/TANKWAGON LOADING	20134
E3LRSICW	SI LOADING RACK	20134
E3NSCRB	E3 SCRUBBER	20134
E3TE3125	STORAGE TANK	20134
E3TE3128	STORAGE TANK	20134
E3TE312	INITIATOR TANK	20134
E3TE313	INITIATOR TANK	20134
E3TE3147	STORAGE TANK	20134
E3TE3148	STORAGE TANK	20134
E3TE3149	STORAGE TANK	20134
E3TE314	INITIATOR TANK	20134
E3TE3150	STORAGE TANK	20134
E3TE3151	ALCOHOL STORAGE TANK	20134
E3TE3152	STORAGE TANK	20134
E3TE3153	STORAGE TANK	20134
E3TE3154	STORAGE TANK	20134
E3TE3155	STORAGE TANK	20134



### New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
E3TE315	INITIATOR TANK	20134
E3TE3357	STORAGE TANK	20134
E3TE3358	STORAGE TANK	20134
E3TE3359	STORAGE TANK	20134
E3TE3360	STORAGE TANK	20134
E3TE3361	STORAGE TANK	20134
E3TE3362	STORAGE TANK	20134
E3TE3363	STORAGE TANK	20134
E3TE3364	STORAGE TANK	20134
E3TE3367	MNP STORAGE TANK	20134
E3TE3368	ALCOHOL STORAGE TANK	20134
E3TE3369	ALCOHOL STORAGE TANK	20134
E3TE3370	ALCOHOL STORAGE TANK	20134
E3TE3371	PRODUCT TANK	20134
E3TE3374	STORAGE TANK	20134
E3TE3375	STORAGE TANK	20134
E3TE3376	STORAGE TANK	20134
E3TE3377	STORAGE TANK	20134
E3TE3378	STORAGE TANK	20134
E3TE3379	DEG TANK	20134
E3TE3380	STORAGE TANK	20134

### New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
E3TE3381	E3 SCRUBBER CIRCULATION TANK	20134
E3TE3385	STORAGE TANK	20134
E3TE3386	STORAGE TANK	20134
E3TE3387	L-SERIES RAW MATERIAL TANK	20134
E3TE3388	LACTIC ACID STORAGE TANK	20134
E3TE3389	SI TANK	20134
E3TE344	STORAGE TANK	20134
E3TE345	STORAGE TANK	20134
E3TE346	STORAGE TANK	20134
E3TE347	STORAGE TANK	20134
E3TE348	STORAGE TANK	20134
E3TE357	STORAGE TANK	20134
E3TE391	STORAGE TANK	20134
E3TE392	STORAGE TANK	20134
E3TE393	STORAGE TANK	20134
E3TE394	STORAGE TANK	20134
E6FE61	REACTOR	20134
E6FE624	REACTOR	20134
E6FE62	REACTOR	20134
E6FE63	REACTOR	20134
E6FE64	REACTOR	20134

### New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
E6FUG	E6 UNIT FUGITIVES	20134
E6LR0SCW	RAILCAR/TANKWAGON LOADING	20134
E6LR0SPC	RAILCAR LOADING	20134
E6LR0SPW	TANKWAGON LOADING	20134
E6NSCRB	E6 SCRUBBER	20134
E6SCRBTk	E6 SCRUBBER CIRCULATION TANK	20134
E6TE610	STORAGE TANK	20134
E6TE611	STORAGE TANK	20134
E6TE614	STORAGE TANK	20134
E6TE61	STORAGE TANK	20134
E6TE6212	STORAGE TANK	20134
E6TE6213	ACETIC ACID TANK	20134
E6TE6214	STORAGE TANK (CAUSTIC)	20134
E6TE628A	STORAGE TANK	20134
E6TE628B	STORAGE TANK	20134
E6TE62	STORAGE TANK	20134
E6TE632	STORAGE TANK	20134
E6TE633	STORAGE TANK	20134
E6TE634	STORAGE TANK	20134
E6TE635	STORAGE TANK	20134
E6TE636	TALLOW AMINE STORAGE TANK	20134

### New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
E6TE637	T-2 STORAGE TANK	20134
E6TE638	PEG STORAGE TANK	20134
E6TE639	TAME-15 BLENDING TANK	20134
E6TE63	STORAGE TANK	20134
E6TE640	T-15 STORAGE TANK	20134
E6TE641	T-15 STORAGE TANK	20134
E6TE64	STORAGE TANK	20134
E6TE651	BLEND TANK	20134
E6TE65	STORAGE TANK	20134
E6TE66	STORAGE TANK	20134
E6TE67	STORAGE TANK	20134
E6TE68	STORAGE TANK	20134
E6TE69	STORAGE TANK	20134
E7RE9803	E7 FLARE	20134
FUG63PPP	FUGITIVES	20134
PROE3FE353	CHEMICAL MANUFACTURING PROCESS	20134
PROE3FE355	CHEMICAL MANUFACTURING PROCESS	20134
PROE3FE356	CHEMICAL MANUFACTURING PROCESS	20134
PROE6FE61	CHEMICAL MANUFACTURING PROCESS	20134
PROE6FE624	CHEMICAL MANUFACTURING PROCESS	20134
PROE6FE62	CHEMICAL MANUFACTURING PROCESS	20134

### **New Source Review Authorization References by Emissions Unit**

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

<b>Unit/Group/Process ID No.</b>	<b>Emission Unit Name/Description</b>	<b>New Source Review Authorization</b>
PROE6FE63	CHEMICAL MANUFACTURING PROCESS	20134
PROE6FE64	CHEMICAL MANUFACTURING PROCESS	20134
UEUL30	COOLING TOWER NO. 5	20134

**Appendix A**

**Acronym List ..... 73**

## Acronym List

The following abbreviations or acronyms may be used in this permit:

ACFM	actual cubic feet per minute
AMOC	alternate means of control
ARP	Acid Rain Program
ASTM	American Society of Testing and Materials
B/PA	Beaumont/Port Arthur (nonattainment area)
CAM	Compliance Assurance Monitoring
CD	control device
CEMS	continuous emissions monitoring system
CFR	Code of Federal Regulations
COMS	continuous opacity monitoring system
CVS	closed vent system
D/FW	Dallas/Fort Worth (nonattainment area)
EP	emission point
EPA	U.S. Environmental Protection Agency
EU	emission unit
FCAA Amendments	Federal Clean Air Act Amendments
FOP	federal operating permit
gr/100 scf	grains per 100 standard cubic feet
HAP	hazardous air pollutant
H/G/B	Houston/Galveston/Brazoria (nonattainment area)
H <sub>2</sub> S	hydrogen sulfide
ID No.	identification number
lb/hr	pound(s) per hour
MACT	Maximum Achievable Control Technology (40 CFR Part 63)
MMBtu/hr	Million British thermal units per hour
NA	nonattainment
N/A	not applicable
NADB	National Allowance Data Base
NESHAP	National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61)
NO <sub>x</sub>	nitrogen oxides
NSPS	New Source Performance Standard (40 CFR Part 60)
NSR	New Source Review
ORIS	Office of Regulatory Information Systems
Pb	lead
PBR	Permit By Rule
PEMS	predictive emissions monitoring system
PM	particulate matter
ppmv	parts per million by volume
PRO	process unit
PSD	prevention of significant deterioration
psia	pounds per square inch absolute
SIP	state implementation plan
SO <sub>2</sub>	sulfur dioxide
TCEQ	Texas Commission on Environmental Quality
TSP	total suspended particulate
TVP	true vapor pressure
U.S.C.	United States Code
VOC	volatile organic compound